AGArangeusa.com

THE AGA LOGE HOOD BY TRADE-WIND



SPECIFICATIONS

Hood Style

Box

MODELS:

36" : **AH3630LGE**
48" : **AH4830LGE**

Product Dimensions:

Hood Width x Depth x Height
36"W x 24"D x 30"H, 42"H or 54"H (600 cfm/8" collar)
48"W x 24"D x 30"H, 42"H or 54"H (1200 cfm/10" collar)

Product Weight:

36"(30"H) : 104 lbs / 36"(42"H) : 122 lbs / 36"(54"H) : 141 lbs
48"(30"H) : 130 lbs / 48"(42"H) : 151 lbs / 48"(54"H) : 172 lbs

Electrical Requirements:

600 CFM models draw approx. 2.7 Amps
1200 CFM models draw approx. 5.4 Amps

Hood Sone Level:

Ranges from 5-7

COLOR FINISH OPTIONS

CLASSIC COLOR COLLECTION

- **Stainless Steel** (SS)
- **Matte Black** (MBL)
- **White** (WHT)
- **Gloss Black** (BLK)
- **Indigo** (IND)
- **Cornwall Green** (CWG)

SOHO COLOR COLLECTION


- **Slate** (SLT)
- **Stone Blue** (STB)
- **Mineral Green** (MG)
- **Carnaby Blue** (CBB)
- **Fawn** (FWN)
- **Piccadilly Red** (PCR)
- **Salcombe Blue** (SAL)
- **Cranberry** (CNB)

TRIM FINISH OPTIONS

- **Brushed Nickel** (BN)
- **Polished Chrome** (PC)
- **Brushed Brass** (BB)
- **Polished Brass** (PB)
- **Antique Brass** (AB)


NOTE: *Due to global sourcing, paint and / or trim may have minor variations*

DIMENSIONAL DRAWINGS



36" FRONT VIEW
(37" WIDTH WITH ½" BANDS)

36" SIDE VIEW



48" FRONT VIEW
(49" WIDTH WITH ½" BANDS)

48" SIDE VIEW

AGArangeusa.com

THE AGA LOGE HOOD BY TRADE-WIND

PRODUCT FEATURES

Quiet Operation
Large 3 speed blower operates at lower RPM reducing the sound level.

Lighting
Bright LED lighting offers natural looking, 3000K color spectrum. The 36" hood features 2 lights, the 48" hood features 3 lights.


Ease of Operation
Electronic touch controls for 3 speed blower and LED lights.

Easy Cleaning
Dishwasher safe, commercial style baffle filters for effectively removing airborne contaminants.


Detergent inlet holes and grease exit holes in baffle filters for superior dishwasher cleaning.

Flexible Installation
Mounting bars at top and bottom allow for attaching to stud supports. Open top and back design for centered duct location or offset top duct and/or rear offset discharge.


Energy Efficient Operation
LED light bulbs draw only 6 watts each and energy efficient motors draw only 2.5 amps.



Rear view showing liner is easily removed and reinstalled for simply mounting of hood shell to the wall



Rear view of standard, centered top venting.
Open top design allowing simple R/L offset top ducting



Rear view of standard, centered rear venting.
Open back design allowing simple R/L offset rear ducting