UPD40N



Colour range
Body

- Blue grey – BG
- Antique white – AW
- White – WH
- Blue – MB
- Stainless steel – SS
- Graphite matt – MG
- Glossy black – BK
- Burgundy red – BU
- Emerald green – EG
- Optional RAL – RA + $ 2800.00

Finishes
Knobs, handles, frames (optional)

- Brass – G
- Copper – P
- Chrome – C
- Burnished – B

Optional solid door version
optional + $ 700.00

Order code: add letter “Q” before the “N” letter

Noblesse frames
optional → p. 138



Available ovens

Electric oven

Primary oven:
UOV 60 M
Maximum input:
3.5 kW

Secondary oven:
UOV 40 E
Maximum input:
2.8 kW

Configurations

	6 burners with fry top*	Induction
		
Electric oven	UPD40FNMP	UPDI406NMP
	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished
	$ 7.690.00	$ 7.990.00

Fuel requirements

	Natural gas / Liquid propane Voltage: 240 Volts Amps: 26	All electric Voltage: 240 Volts Amps: 74

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

- Bridge induction zone — Ø 7" 1/4 + Ø 7" 1/4 — 1.85 / 2.5 kW + 1.85 kW
- Induction zone — Ø 5" 3/4 — 1.4 / 1.8 kW
- Induction zone — Ø 7" 1/4 — 1.85 / 2.5 kW
- Induction zone — Ø 8" 11/16 — 2.3 / 3.2 kW
- Double ring Dual burner — 25000 btu/h / 900 btu/h
- Griddle — 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h
- Big burner — 10500 btu/h / 2000 btu/h
- Small burner — 7000 btu/h / 1400 btu/h

Complements & accessories

Hood	UAG40	Hood	UANB40	Ladle holder panel	AM4-100
	$ 2.190.00	Brass/Copper/Chrome/Burnished	$ 5.559.00		$ 313.00

Technical drawing & dimensions

